



**mm PT9510**

**Description**

- Absolute Linear Position to 550 inches (1400 cm)
- Aluminum or Stainless Steel Enclosure Options
- VLS Option To Prevent Free-Release Damage
- IP68 • NEMA 6 Protection • Hazardous Area Certification



The PT9510 can operate from an unregulated 14.5 to 40 VDC power supply while providing a regulated output signal over it's full extended range. It provides a 0 - 5 or 0 - 10 VDC position feedback signal proportional to the linear movement of it's stainless steel measuring cable.

As a member of our innovative family of NEMA-4 rated cable-extension transducers, the PT9510 offers numerous benefits. It installs in minutes, functions properly without perfectly parallel alignment, and when its cable is retracted, it measures only 6".

**GENERAL**

Full Stroke Range Options (on this datasheet)	0-75 to 0-550 inches
Output Signal Options	0...10, 0...5, -5...+5, -10...+10 VDC
Accuracy	± 0.12% full stroke
Repeatability	± 0.05% full stroke
Resolution	essentially infinite
Measuring Cable Options	stainless steel or thermoplastic
Enclosure Material	powder-painted aluminum or 303 stainless steel
Sensor	plastic-hybrid precision potentiometer
Potentiometer Cycle Life	≥ 250,000
Maximum Retraction Acceleration	see ordering information
Maximum Velocity	see ordering information
Weight, Aluminum (Stainless Steel) Enclosure	8 lbs. (16 lbs.) max.

**ENVIRONMENTAL**


Enclosure	NEMA 4/4X/6, IP 67/68
Operating Temperature	-40° to 200°F (-40° to 90°C)
Vibration	up to 10 g to 2000 Hz maximum

**EMC COMPLIANCE PER DIRECTIVE 89/336/EEC**


Emission / Immunity	EN50081-2 / EN50082-2
---------------------	-----------------------

**ELECTRICAL**

Input Voltage	14.5-40VDC (10.5-40VDC for 0-5 volt output)
Input Current	10 mA maximum
Output Impedance	1000 ohms
Maximum Output Load	5000 ohms
Output Signal, Zero Adjust	up to 50% of full stroke range
Output Signal, Span Adjust	to 50% of factory set span





**Output signal**





\*Additional Output Options: 0...5, -5...+5, -10...+10 Vdc

01.2016 | version 20140624 - Rev.11

Fig. 1 – Outline Drawing (18 oz. cable tension only)



A DIMENSION (INCHES)				
MEASURING CABLE				
RANGE	Ø.031 in.	Ø.034 in.	Ø.047 in.	Ø.062 in.
75	n/a	0.22	0.29	0.37
100	n/a	0.29	0.39	0.49
150	n/a	0.44	0.59	0.73
200	n/a	0.58	0.79	0.98
250	n/a	0.73	0.98	1.22
300	n/a	0.88	1.18	1.47
350	n/a	1.02	1.38	1.71
400	n/a	1.17	1.57	1.96
450	n/a	1.31	1.77	n/a
500	n/a	1.46	1.97	n/a
550	1.61	1.61	n/a	n/a



DIMENSIONS ARE IN INCHES [MM]  
tolerances are 0.03 IN. [0.5 MM] unless otherwise noted.

\* tolerance = +.005 - .001 [+13 - .03]  
\*\* tolerance = +.005 - .005 [+13 - 13]

**Ordering information**

**Model Number**

PT9510-      -      -      -      -      -      -      -     

order code:      R      A      B      C      D      E      F      G

Sample Model Number:

PT9510 - 0500 - 111 - 1110

- R range: 500 inches
- A enclosure/cable tension: aluminum/18 oz.
- B measuring cable: .034 nylon-coated stainless front
- C cable exit: 0..10 vdc
- E output signal: 0..10 vdc
- F electrical connection: 6-pin plastic connector

**Full Stroke Range**


R order code:	0075	0100	0150	0200	0250	0300	0350	0400	0450*	0500*	0550*
full stroke range, min:	in.	100 in.	150 in.	200 in.	250 in.	300 in.	350 in.	400 in.	450 in.	500 in.	550 in.

\* - 36 oz. cable tension strongly recommended


■ Ordering Information (cont.)

## Enclosure Material and Measuring Cable Tension

A order code:	1	3	2	4
tension ( $\pm 30\%$ ):	18 oz.		36 oz.	
enclosure material:	powder-painted aluminum	303 stainless steel	powder-painted aluminum	303 stainless steel
max. acceleration:	1 G	.33 G	5 G	2 G
max. velocity:	60 inches/sec	20 inches/sec	200 inches/sec	80 inches/sec



standard housing  
see fig 1.



dual-spring housing  
see fig 2.

## Measuring Cable

B order code:	1	2	3	4
cable construction:	$\emptyset$ .034-inch nylon-coated stainless steel rope	$\emptyset$ .047-inch bare stainless steel rope	$\emptyset$ .058-inch PVC jacketed vectra fiber rope	$\emptyset$ .031-inch bare stainless steel rope
available ranges:	all ranges	all ranges up to 500 inches	all ranges up to 400 inches	550-inch range only
general	indoor	outdoor, debris, high temperature	high voltage or magnetic field	outdoor, debris, high temperature

## Cable Exit





C Ordercode:	1	2	3	4
	front	top	back	down




## Output Signals

E order code:	1	2	3	4	5	6	7	8
output signal options:	0...10 VDC	10...0 VDC	0...5 VDC	5...0 VDC	-10...+10 VDC	+10...-10 VDC	-5...+5 VDC	+5...-5 VDC
input voltage: span adjustment: zero adjustment:	0 $\blacktriangle$ 10	10 $\blacktriangleright$ 0	0 $\blacktriangle$ 5	5 $\blacktriangleright$ 0	-10 $\blacktriangle$ +10	+10 $\blacktriangleright$ -10	-5 $\blacktriangle$ +5	+5 $\blacktriangleright$ -5
	14.5 – 40 vdc	to 50% of full stroke range from factory set zero to 50% of full stroke range	10.5 – 40 vdc		14.5 – 40 vdc	to 75% of full stroke range from factory set zero to 25% of full stroke range	10.5 – 40 vdc	
example:	ordercode = 1 = 0...10 VDC $\rightarrow$				0 vdc =	10 vdc =		

Ordering Information (cont.)


Electrical Connection

Order code:	1	2	3	4
	6-pin plastic connector w/mating plug IP 67, NEMA 4X**,6	10-ft. [3 M] waterproof cable IP 67, NEMA 4X**, 6	6-pin metal connector w/mating plug IP 65, NEMA 4	25-ft. [7.5 M] instrumentation cable IP 67, NEMA 6
	 1/2 - 5/16" [14 - 8 mm] cable dia. 16 AWG max conductor size connector: MS3102E-14S-6P mating plug: MS3106E-14S-6S	 10 ft. x 0.4-in. dia. [3 M x 10 mm dia.] 18 AWG, type SJOW	 3/8-in. [9 mm] max cable dia. 16 AWG max conductor size connector: MS3102E-14S-6P mating plug: MS3106E-14S-6S	 25 ft. x 0.2-in. dia. [7,5 M x 5 mm dia.] 24 AWG, shielded

Order code:	5	6	7
	100-ft. [30 M] waterproof cable IP 67, NEMA 4X**,6	10-ft. [3 M] pressure tested* waterproof cable IP 68, NEMA 4X**, 6P	100-ft. [30 M] pressure tested* waterproof cable IP 68, NEMA 4X**, 6P
	 100 ft. x 0.4-in. dia. [30 M x 10 mm dia.] 18 AWG, type SJTOW	 10 ft. x 0.4-in. dia. [3 M x 10 mm dia.] 18 AWG, type SJTOW	 100 ft. x 0.4-in. dia. [30 M x 10 mm dia.] 18 AWG, type SJTOW

**6-pin Mating Plug**

pin	signal
A	input voltage
B	output signal
C	common



**Waterproof Cable**


color code	signal
WHITE	input voltage
GREEN	output signal
BLACK	common

**Instrumentation Cable**


color code	signal
RED	input voltage
GREEN	output signal
BLACK	common

Notes: { \* -Test pressure: 100 feet [30 meters] H<sub>2</sub>O (40 PSID); Test Me<sub>dium</sub>: Air; Duration: 2 hours.  
\*\* -NEMA 4X applies to stainless steel enclosure only.

Output Signal Selection (does not apply to -5...+5 & -10...+10 vdc options)




To gain access to the signal board, remove four Allen-Head Screws and remove end cover bracket.




**Caution! Do Not Remove Spring-Side End Cover**  
Removing spring-side end cover could cause spring to become unseated and permanently damaged.

The output signal direction can be reversed at any time by simply changing the dip-switch settings found on the internal signal board. After the settings have been changed, adjustment of the Zero and Span trimpots will be required to precisely match signal values to the beginning and end points of the stroke.


Fig. 2 – Outline Drawing (36 oz. cable tension only)



**mounting hole detail**




**eyelet detail**



**A DIMENSION (INCHES)**

RANGE	MEASURING CABLE			
	Ø.031 in.	Ø.034 in.	Ø.047 in.	Ø.062 in.
75	n/a	0.22	0.29	0.37
100	n/a	0.29	0.39	0.49
150	n/a	0.44	0.59	0.73
200	n/a	0.58	0.79	0.98
250	n/a	0.73	0.98	1.22
300	n/a	0.88	1.18	1.47
350	n/a	1.02	1.38	1.71
400	n/a	1.17	1.57	1.96
450	n/a	1.31	1.77	n/a
500	n/a	1.46	1.97	n/a
550	1.61	1.61	n/a	n/a



DIMENSIONS ARE IN INCHES [MM]  
tolerances are 0.03 IN. [0.5 MM] unless otherwise noted.

\* tolerance = +.005 - .001 [+ .13 - .03]  
\*\* tolerance = +.005 - .005 [+ .13 - .13]

**VLS Option - Free Release Protection**

The patented Velocity Limiting System (VLS) is an option for PT9000 Series cable extension transducers that limits cable retraction to a safe 40 to 55 inches per second for the single spring option and 40 to 80 inches per second for the higher tension dual spring option.

The VLS option prevents the measuring cable from ever reaching a damaging velocity during an accidental free release. This option is ideal for mobile applications that require frequent cable disconnection and reconnection. It prevents expensive unscheduled downtime due to accidental cable mishandling or attachment failure.

**How To Configure Model Number for VLS Option:**



creating VLS model number (example)...

1. select PT9510 model
2. remove "PT" from the model number
3. add "VLS"
4. completed model number !

PT9510-0100-111-1110  
~~PT~~9510-0100-111-1110 VLS  
 + 9510-0100-111-1110  
 VLS9510-0100-111-1110

The information provided herein is to the best of our knowledge true and accurate, it is provided for guidance only. All specifications are subject to change without prior notification.